

PAROC AluCoat Tape



Short Description

PAROC AluCoat Tape is a reinforced aluminum foil tape with pressure sensitive, low temperature acrylic adhesive, siliconized release paper liner and AluCoat printing.

Application

Ideal for sealing joints when using PAROC AluCoat products such as sections, lamella mats or slabs. PAROC Tape AluCoat gives a great finish and safe installation.

Width

50, 75 and 100 mm

Length

50 m

Volume

Rolls / carton: 50mm / 24 pcs, 75mm / 16 pcs, 100mm / 8 pcs. 24 cartons/pallet.

Other Properties

Other Properties	
Property	Value
Adhesive	Low temperature acrylic
.	
Release liner	Siliconized paper
.	
Temperature range	-35 °C to +120 °C
.	
Storage conditions	+18 °C ÷ 25 °C, under dry conditions inside a warehouse
.	
Installation temperature	-20 °C ÷ 40 °C

Facings

Facing Material

Background: Reinforced aluminum foil

Colours

Aluminum, bright with AluCoat printing

Installation

During the installation, the insulation material to be taped should be at a minimum temperature of +5 Celsius. Allow the temperature of the insulating material to adjust to the ambient installation temperature. Make sure that the surfaces to be joined with tape are clean, dry free of dust and grease. Surface must be free from oil, fat, dust and solvents before film/tape application. Do not use cleaners containing anti-adhesive agents. Some plastics and paints may discharge anti-adhesive agents leading to bonding failure. Rough and uneven surfaces may weaken bonding.

Handling and Storage

Product should be stored in original packaging, laid flat on the slit edge of the roll. Storage in dry and clean areas, at normal temperature, protected from direct sunlight and heat sources.

More Information

We strongly advise users to test the product 's suitability for their own particular requirement. All data and recommendations contained in this Technical Data Sheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate tape for a given application. This information is provided without liability. We reserve the right to change the technical specification without prior notice.

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).